



# Material Safety Data Sheet

G11E03

Revision Date: 09/16/2011

Issuing Date: 09/16/2011

## CHARMIAN COLORED ROOFING GRANULES

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Company/Undertaking Identification:** Specialty Granules Inc.  
13424 Pennsylvania Avenue  
Suite 303  
Hagerstown, MD 21742  
Telephone: (301)-733-4000  
Fax: (301)-733-4003

**Emergency Telephone:** CHEMTREC: 1-800-424-9300 or 703-527-3887 (Outside of the USA)  
(Spill Related Emergencies)  
PROSAR: 1-800-241-7439 (Health Related Emergencies)

**Prepared By:** Product Stewardship

**Product Code:** G11E03

**Product Name:** CHARMIAN COLORED ROOFING GRANULES

**CAS Name:** NA

**Synonyms:** Metabasalt coated with pigments, sodium silicate, kaolin clay, oil and siloxane

**Product Use Description:** Roofing materials

### 2. HAZARDS IDENTIFICATION

#### Emergency Overview

No Hazards Known.

#### Hazard Summary

**Target Organs:** • None effected.

**Primary Routes of Entry:** Not applicable.

**Acute Health Hazard:** None known.

**Chronic Health Hazard:** None known

#### Symptoms of Overexposure

**Eye Contact:** Not hazardous

**Skin contact:** Not hazardous

**Ingestion:** Not hazardous

**Inhalation:** Not hazardous

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components:	Weight %
Iron oxide 1309-37-1	<1
Chrome oxide 1308-38-9	<1

G11E03

Kaolin Clay 1332-58-7	0-6
Titanium dioxide 13463-67-7	<3
Carbon black 1333-86-4	<1

#### 4. FIRST AID MEASURES

<b>Eye Contact:</b>	Flush with plenty of water.
<b>Skin Contact:</b>	Wash off with soap and water.
<b>Ingestion:</b>	Do not induce vomiting. If conscious, give 2 glasses of water. Get immediate medical attention.
<b>Inhalation:</b>	Not hazardous by inhalation. Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion. Get medical attention if symptoms occur.

#### 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media:** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment

**Combustion/Explosion Hazards:** None Known

**Special Protective Equipment For Fire-Fighters:** Wear self-contained breathing apparatus and protective suit.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Wear suitable protective equipment.

**Methods for Cleaning Up:** Soak up with inert absorbent material.

#### 7. HANDLING AND STORAGE

**Handling:** Avoid breathing dust. Wash thoroughly after handling.

**Storage:** Store in sealed containers in a protected area.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Measures:** Use only in well-ventilated areas.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn

**Hand Protection:** Wear protective gloves.

**Eye Protection:** Safety glasses.

**Exposure Limits:**

Components:	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)	U.S. - OSHA - Final PELs - Time Weighted Averages (TWAs)
Iron oxide 1309-37-1 (<1)	5mg/m <sup>3</sup> TWArespirable fraction	10 mg/m <sup>3</sup> fume

Components:	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)	U.S. - OSHA - Final PELs - Time Weighted Averages (TWAs)
Chrome oxide 1308-38-9 (<1 )	No TLV/TWA Established	No TLV/TWA Established
Kaolin Clay 1332-58-7 (0-6 )	2mg/m <sup>3</sup> TWAparticulate matter containing no asbestos and <1% crystalline silica, respirable fraction	15 mg/m <sup>3</sup> total dust 5 mg/m <sup>3</sup> respirable fraction
Titanium dioxide 13463-67-7 (<3)	10mg/m <sup>3</sup> TWA	15 mg/m <sup>3</sup> total dust
Carbon black 1333-86-4 (<1 )	3mg/m <sup>3</sup> TWAINhalable fraction	3.5 mg/m <sup>3</sup>

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical State:</b>	Granules
<b>Color:</b>	Not determined
<b>Odor:</b>	Not determined
<b>Odor Threshold:</b>	Not available
<b>pH:</b>	Not determined
<b>Specific Gravity:</b>	3.0
<b>Boiling Point (°F):</b>	Not determined
<b>Melting/Freezing Point (°F):</b>	>2,300
<b>Vapor Pressure:</b>	Not determined
<b>Solubility:</b>	Negligible
<b>Flash Point (°F):</b>	Not determined

## 10. STABILITY AND REACTIVITY

<b>Chemical Stability:</b>	Stable under normal conditions.
<b>Conditions to Avoid:</b>	None known

## 11. TOXICOLOGICAL INFORMATION

### Toxicity Test:

### Carcinogenicity:

Components:	IARC Monographs on Occupational Exposures to Chemical Agents List -	NTP Report on Carcinogens List -	U.S. - OSHA - Carcinogens
Titanium dioxide 13463-67-7 (<3)	Group 2B (Possibly Carcinogenic to Humans)		Listed
Carbon black 1333-86-4 (<1 )	Group 2B (Possibly Carcinogenic to Humans)		Listed

### Other Information

Silica is chemically and biologically inert when ingested. inhalation of silica dust may cause silicosis and/or cancer. >15,000 (probable human LDLo for silica)

## 12. ECOLOGICAL INFORMATION

<b>Persistence and Degradability:</b>	Not determined.
<b>Ecotoxicity:</b>	Not determined

### 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Methods:** Dispose of in accordance with local regulations.

### 14. TRANSPORT INFORMATION

**Land Transport:**

*DOT (Non-Bulk):*

Not regulated DOT

*DOT (Bulk):*

**Air Transport (IATA):**

Not regulated IATA

**Sea Transport (IMO):**

Not regulated IMDG

**TDG (Canada):**

Not regulated TDG

### 15. REGULATORY INFORMATION

Inventories	Status
TSCA	Not Listed
DSL	Not Listed
NDSL	Not Listed
ENCS	Not Listed
AICS	Not Listed
EINECS	Not Listed
ELINCS	Not Listed
NZIoC	Not Listed
KECI	Not Listed
PICCS	Not Listed
IECSC	Not Listed

**California Proposition 65  
Carcinogens & Reproductive  
Toxicity (CRT) List:**

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects.

Components:	California Proposition 65
Carbon black 1333-86-4 (<1 )	carcinogen

**EPCRA (SARA Title III):** Not applicable

**WHMIS Ingredient Disclosure List:** One or more components of this product is listed on the WHMIS Ingredient Disclosure list.

## 16. OTHER INFORMATION

**NFPA Rating:** HEALTH 1, FLAMMABILITY 0 , REACTIVITY 0.

**HMIS RATING:**

<b>HEALTH</b>	1
<b>FLAMMABILITY</b>	0
<b>PHYSICAL HAZARD</b>	0

**Prepared By:** Product Stewardship

**MSDS sections updated:** This data sheet contains changes from the previous version in section(s) 1,16

**Legend:** N.Av.= Not Available; N.A.= Not Applicable

**Disclaimer:** For purposes of this MSDS, Specialty Granules Inc., as responsible party, provides the information herein which is intended for use by persons who have or should obtain professional knowledge and experience in the subjects discussed. SGI's industrial products are used as materials in the production of products by industrial customers. Specialty Granules Inc. usually has only limited information about the products of its customers and their composition, methods of manufacture and use. Accordingly, SPECIALTY GRANULES INC. MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS OR RELIABILITY OF INFORMATION HEREIN EXCEPT THAT SUCH INFORMATION IS, TO THE BEST OF SGI'S KNOWLEDGE AND BELIEF, ACCURATE AS OF THE DATE INDICATED. Specialty Granules Inc. recommends that customers independently test and evaluate its products and their products and processes in which SGI products are used in order to decide their safety and effectiveness.

**\*\*\*End of Safety Data Sheet\*\*\***